



CYCLONE™ ULTRA

*Electric Portable Aerosol Applicator
 (ULV SPRAYER)*

Dispenses BOTH Oil and Water-based Products

The Cyclone Ultra with its 2-stage blower and rugged metering valve assures particles under 20 microns regardless of flow rate and viscosity of material. Ideal for pest control work in areas such as hospitals, nursing homes, schools, apartment buildings, restaurants, greenhouses, etc.

The spray head adjustable 45° up and down and will project the spray droplets up to 60' (20 m) when held stationary

MODELS

Model 2734 Cyclone 110 Volt.

Model 2736 Cyclone 220 Volt.

SPECIFICATIONS

Adjustable flow rates:	0-3 oz/min, or 0-90 ml/min.
Particle size:	7.5-20 microns.
Tank capacity:	1 gallon (3.8 liters).
Length:	16 in or 40.6 cm.
Width:	10.25 in or 26 cm
Height:	16 in or 40.6 cm
Weight (Empty):	9.3 lbs. or 4.2 kg

INPUT POWER:

Models 2734: 110/120 volt AC, 8.5 Amps, 50/60 Hz

Models 2736: 210/250 volt AC, 4.2 Amps, 50/60 Hz

SHIPPING DATA:

L x W x H: 22 x 12 x 17 (in) or 55 x 30x 43 (cm)

Weight: 14 lbs. or 7.26 kg

Volume: 2.6 Cu. Ft or 0.073 cu. M.

Weight with optional float tank: 10 lbs. (4.54 kg)

DISTRIBUTED BY:

Authorized Exclusive Distributor in Laos:

SKN Trading Import Export Sole Co.,Ltd.
 No.42, 23 Singha Road,
 Ban Phonxay, Muong Saysetha
 Vientiane, LAOS
 Hotline: +856 (0) 20 9992 6688
 Email: sales@sknlaos.com



Cyclone Ultra-Flex

An 18 inch (46 cm) flexible hose with handle on nozzle permits spraying into normally inaccessible and hard to reach areas such as under/between kitchen cabinets, under carpets and above ceilings.

The Flex Hose unit is ideal for general pest control and duct work that requires disinfectant or duct sealant applications.

MODELS

Model 3000 Cyclone Ultral Flex 110 Volt.

Model 3004 Cyclone Ultral Flex 220 Volt.



ONE YEAR LIMITED WARRANTY